최종 검사 성적서

담 당	검 토	결 재
	전 결 완 료	

제품명: 자동세정건조식변기

기 종: 로얄&컴퍼니	LOT생산일	LOT검사일	LOT 크기	LOT 구분	시료수
RB-2400	2017.04.11~12	2017.04.13	500	170D402839~3338	30
온수기 정격전압 220 V소비 전력 600W옥내용					

변좌 정격전압 220 V소비 전력 55W	LOT 판정	합격	경	중	치명
전기용품안전인증등록번호 :ERI JH07454-12001	합격	O			

항 목		규 격										
제조 번호		포장SER NO		2017.04.11	2017.04.11	2017.04.12	2017.04.12	2017.04.12	2017.04.12	2017.04.12	2017.04.12	2017.04.12
		제조 SER NO		170D4 02845	170D4 02902	170D4 02970	170D4 03021	170D4 03085	170D4 03153	170D4 03191	170D4 03247	170D4 03277	170D4 03316
절연저항		DC 500V 10mΩ이상		∞	∞	∞	∞	∞	∞	∞	∞	∞	∞
내전압		1500/1초 10mA이하		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
소비전력	제품종합	630W -700w		663	657	653	658	657	662	661	657	653	643
	온수기	540W - 630W		607	602	601	599	604	607	599	602	604	594
	변좌	49.5 - 60.5W		55	56	55	55	55	55	55	55	55	55
	건조	84W - 170W		161	165	163	163	163	163	164	166	164	162
노즐 동작	물분사시 노즐막힘이 없고 원활할 것.		세정(60 -100)	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
			비데(60 -100)	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
			쾌변(70 -110)	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
누설전류		0.25mA 이하일 것		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
기능동작		동작시 이상이 없을 것		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
변좌 온도		41 ±2℃		39.4도	40.2도	39.8도	39.8도	39.7도	39.8도	39.5도	39도	39.8도	39도
온수온도 유지시간		-5℃까지30초이상		39초	39초	41초	39초	41초	39초	39초	39초	41초	39초
온수온도		40℃ (+1, -2)		40도	39.3도	39.6도	39도	39.2도	40.2도	39.7도	39도	39.2도	40도
세정 동작시험		1분동작		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
접지저항		25A 1분간 인가 시 0.1Ω이하		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
착좌센서동작확인		이상이 없을 것		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
변좌 개폐 시간		3초-15초	변좌	6초	6초	6초	5초	5초	7초	8초	6초	7초	7초
			카바	5초	9초	9초	7초	5초	9초	5초	7초	6초	8초
내압 성능		17.5kg에서1분간견딜것		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
코드 유효장		1500 +100		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
자동 물내림		11초 이내		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
자동 물내림		기본설정		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
Flushing 유량 Test		실측값 [L/Min]		6L	6L	6L	6L	6L	6L	6L	6L	6L	6L
수동 물내림 장치		동작 확인		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
외 관		이상 없을것		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
구 조		이상 없을것		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
표 시		이상 없을것		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
포 장		이상 없을것		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK

항목	규 격										
라벨류	LABEL COVER FLUSHING		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	LABEL FLUSHING		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	SIDE KEY		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	CAUTION		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	LABEL SENSOR		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	LABEL RATING		OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
부속품	사용설명서	1	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	리모컨(브라켓)	1	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	건전지	3	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	스크류	3	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	반원형 플레이트	1	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	급수 파이프	1	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	물잠금 밸브(고무 패킹)	1	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	급수필터	1	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
	급수 호스	1	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK

비 고

▪ 온수온도 유지시간 1日 1대 측정.

▪ 급수온도 : 12도 ▪ 주위온도 : 22도

★ 비데 양측면 IR 수신방식 적용.

★ 소형 리모컨, IR 타입 적용.